

# BNC CORDSETS STRAIGHT & COILED

## BNC TO BNC


### Example Cordset: CB104-F-010-F

Black polyurethane jacketed coiled cable, with BNC plug connector to BNC plug connector, 10 foot length extended



### Example Cordset: CB103-F-005-F-SF

Black polyurethane jacketed cable, with BNC plug connector to BNC plug connector, with safety connector, 5 foot length



Cable Type <small>(see Cables data sheet)</small>	Connector Part Number <small>(see Factory Installed Connectors data sheet)</small>	Cable Length <small>(three digit format)</small>	Terminating Connector Part Number <small>(see Factory Installed Connectors data sheet)</small>	Safety Connector <small>(see page 65 for Safety Connector information)</small>
<p><b>CB103</b></p> <p>Black Polyurethane 2 Conductor Braided Shield with Drain Wire 250°F (121°C) .245 in (6 mm) AWG=20</p>	<p><b>E</b></p> BNC Jack Connector Portable Measurements, Permanent Mount	<p><b>Select Cable Length Based on Three Digit Numbering System</b></p> <p><b>Example Numbering:</b></p> <p>001 = 1 ft. (.30 m) 005 = 5 ft. (1.52 m) 010 = 10 ft. (3.05 m) 015 = 15 ft. (4.57 m) 025 = 25 ft. (7.62 m) 050 = 50 ft. (15.24 m) 100 = 100 ft. (30.48 m)</p> <p>Straight Cables Available in Custom Lengths</p>	<p><b>E</b></p> BNC Jack Connector Portable Measurements, Permanent Mount	<p><b>SF</b></p> Break-Away Safety Connector
<p><b>CB104</b></p> Black Polyurethane, Coiled 2 Conductor Braided Shield 250°F (121°C) .210 in (5 mm) AWG = 22	<p><b>F</b></p> BNC plug connector Portable Measurements, Permanent Mount		<p><b>F</b></p> BNC plug connector Portable Measurements, Permanent Mount	
<p><b>CB108</b></p> Black Polyurethane, Light weight, Coiled 2 Conductor Braided Shield 250°F (121°C) .170 in (4 mm) AWG = 24	<p><b>EX</b></p> BNC Jack Connector, Epoxy Filled Portable Measurements, Permanent Mount	<p><b>Coiled Cables Available in the Following Lengths Only:</b></p> <p>006 = 6 ft. (1.83 m) 010 = 10 ft. (3.05 m) 016 = 16 ft. (4.88 m)</p>	<p><b>EX</b></p> BNC Jack Connector Portable Measurements, Permanent Mount	
<p><b>CB110</b></p> Black Polyurethane, Light weight, 2 Conductor Braided Shield with Drain Wire 250°F (121°C) .175 in (4 mm) AWG = 20	<p><b>FX</b></p> BNC plug connector, Epoxy Filled Portable Measurements, Permanent Mount		<p><b>FX</b></p> BNC Plug Connector, Epoxy Filled Portable Measurements, Permanent Mount	
	<p><b>FX90</b></p> BNC plug connector, Epoxy Filled, Right Angle Portable Measurements, Permanent Mount		<p><b>FX90</b></p> BNC plug connector, Epoxy Filled, Right Angle Portable Measurements, Permanent Mount	