

ADASH COMPATIBLE DATA COLLECTOR CORDSETS

A4300 & NRS VA3


Example Cordset: CB108-C84-010-D2C













Light weight, black polyurethane jacketed coiled cable, with 7 pin connector to 2 socket MIL connector, 10 foot length extended



Example Cordset: CB110-C84-005-D2C-SF

Light weight, black polyurethane jacketed cable, with 7 pin connector to 2 socket MIL connector, with safety connector, 5 foot length



Cable Type (see Cables data sheet)	Connector Part Number (see Factory Installed Connectors data sheet)	Cable Length (three digit format)	Terminating Connector Part Number (see Factory Installed Connectors data sheet)	Safety Connector (see page 65 for Safety Connector information)
<p>CB103</p>  <p>Black Polyurethane 2 Conductor Braided Shield with Drain Wire 250° F (121° C) .245 in (6 mm) AWG=20</p>	<p>C84</p>  <p>7 Pin Connector Portable Measurements</p>	<p>Select Cable Length Based on Three Digit Numbering System</p> <p>Example Numbering:</p> <p>001 = 1 ft. (,30 m) 005 = 5 ft. (1,52 m) 010 = 10 ft. (3,05 m) 015 = 15 ft. (4,57 m) 025 = 25 ft. (7,62 m) 050 = 50 ft. (15,24 m) 100 = 100 ft. (30,48 m)</p> <p>Straight Cables Available in Custom Lengths</p>	<p>D2C</p>  <p>2 socket MIL connector Portable Measurements</p>	<p>SF</p>  <p>Break-Away Safety Connector</p>
<p>CB104</p>  <p>Black Polyurethane, Coiled 2 Conductor Braided Shield 250°F (121°C) .210 in (5 mm) AWG = 22</p>		<p>Coiled Cables Available in the Following Lengths Only:</p> <p>006 = 6 ft. (1,83 m) 010 = 10 ft. (3,05 m) 016 = 16 ft. (4,88 m)</p>	<p>E</p>  <p>BNC Jack Connector Portable Measurements, Permanent Mount</p>	
<p>CB108</p>  <p>Black Polyurethane, Light weight, Coiled 2 Conductor Braided Shield 250°F (121°C) .170 in (4 mm) AWG = 24</p>			<p>F</p>  <p>BNC plug connector Portable Measurements, Permanent Mount</p>	
<p>CB110</p>  <p>Black Polyurethane, Light weight, 2 Conductor Braided Shield with Drain Wire 250°F (121°C) .175 in (4 mm) AWG = 20</p>			<p>J2C</p>  <p>2 Socket mini-MIL Connector Portable Measurements</p>	
			<p>K2C</p>  <p>2 Socket MIL Connector Portable Measurements</p>	
			<p>R2C</p>  <p>2 Pin MIL Connector Portable Measurements, Permanent Mount</p>	

