

BENTLY NEVADA COMPATIBLE DATA COLLECTOR CORDSETS

BENTLY SNAPSHOT™

SECTION 2 - CABLES & CONNECTORS
Data Collector Cordsets

Example Cordset: CB104-C96-010-D2C













Black polyurethane jacketed coiled cable, with 10 pin Fischer® connector to 2 socket MIL connector, 10 foot length extended



Example Cordset: CB103-C96-015-D2C-SF

Black polyurethane jacketed cable, with 10 pin Fischer® connector to 2 socket MIL connector, with safety connector, 15 foot length



CB <input type="text"/> <input type="text"/> <input type="text"/> - <input type="text"/> - <input type="text"/> <input type="text"/> <input type="text"/> - <input type="text"/> - <input type="text"/> <input type="text"/>	Connector Part Number (see <i>Factory Installed Connectors</i> data sheet)	Cable Length (three digit format)	Terminating Connector Part Number (see <i>Factory Installed Connectors</i> data sheet)	Safety Connector (see <i>page 65</i> for Safety Connector information)
<p>CB103</p>  <p>Black Polyurethane 2 Conductor Braided Shield with Drain Wire 250°F (121°C) .245 in (6 mm) AWG=20</p> <p>CB104</p>  <p>Black Polyurethane, Coiled 2 Conductor Braided Shield 250°F (121°C) .210 in (5 mm) AWG = 22</p> <p>CB108</p>  <p>Black Polyurethane, Light weight, Coiled 2 Conductor Braided Shield 250°F (121°C) .170 in (4 mm) AWG = 24</p> <p>CB110</p>  <p>Black Polyurethane, Light weight, 2 Conductor Braided Shield with Drain Wire 250°F (121°C) .175 in (4 mm) AWG = 20</p>	<p>C96</p>  <p>10 pin Fischer® or Equivalent Connector, acceleration input Portable Measurements</p>	<p>Select Cable Length Based on Three Digit Numbering System</p> <p>Example Numbering:</p> <p>001 = 1 ft. (.30 m) 005 = 5 ft. (1.52 m) 010 = 10 ft. (3.05 m) 015 = 15 ft. (4.57 m) 025 = 25 ft. (7.62 m) 050 = 50 ft. (15.24 m) 100 = 100 ft. (30.48 m)</p> <p>Straight Cables Available in Custom Lengths</p> <p>Coiled Cables Available in the Following Lengths Only:</p> <p>006 = 6 ft. (1.83 m) 010 = 10 ft. (3.05 m) 016 = 16 ft. (4.88 m)</p>	<p>D2C</p>  <p>2 socket MIL connector Portable Measurements</p> <p>E</p>  <p>BNC Jack Connector Portable Measurements, Permanent Mount</p> <p>F</p>  <p>BNC plug connector Portable Measurements, Permanent Mount</p> <p>J2C</p>  <p>2 Socket mini-MIL Connector Portable Measurements</p> <p>K2C</p>  <p>2 Socket MIL Connector Portable Measurements</p> <p>R2C</p>  <p>2 Pin MIL Connector Portable Measurements, Permanent Mount</p>	<p>SF</p>  <p>Break-Away Safety Connector</p>

Backed by our Unconditional Lifetime Warranty

www.ctconline.com

