

DIAGNOSTIC INSTRUMENTS COMPATIBLE DATA COLLECTOR CORDSETS

DI-225-D

SECTION 2 - CABLES & CONNECTORS
Data Collector Cordsets

Example Cordset: CB104-C66-010-D2CG











Black polyurethane jacketed coiled cable, with 6 pin Fischer® connector to 2 socket MIL connector, 10 foot length extended



Example Cordset: CB103-C66-005-D2CG-SF

Black polyurethane jacketed cable, with 6 pin Fischer® connector to 2 socket MIL connector, with safety connector, 5 foot length



CB Cable Type (see Cables data sheet)	Connector Part Number (see Factory Installed Connectors data sheet)	Cable Length (three digit format)	Terminating Connector Part Number (see Factory Installed Connectors data sheet)	Safety Connector (see page 65 for Safety Connector information)
<p>CB103</p>  <p>Black Polyurethane 2 Conductor Braided Shield with Drain Wire 250°F (121°C) .245 in (6 mm) AWG=20</p> <p>CB104</p>  <p>Black Polyurethane, Coiled 2 Conductor Braided Shield 250°F (121°C) .210 in (5 mm) AWG = 22</p> <p>CB108</p>  <p>Black Polyurethane, Light weight, Coiled 2 Conductor Braided Shield 250°F (121°C) .170 in (4 mm) AWG = 24</p> <p>CB110</p>  <p>Black Polyurethane, Light weight, 2 Conductor Braided Shield with Drain Wire 250°F (121°C) .175 in (4 mm) AWG = 20</p>	<p>C66</p>  <p>6 pin circular Fischer® or equivalent connector Portable Measurements</p>	<p>Select Cable Length Based on Three Digit Numbering System</p> <p>Example Numbering:</p> <p>001 = 1 ft. (.30 m) 005 = 5 ft. (1.52 m) 010 = 10 ft. (3.05 m) 015 = 15 ft. (4.57 m) 025 = 25 ft. (7.62 m) 050 = 50 ft. (15.24 m) 100 = 100 ft. (30.48 m)</p> <p>Straight Cables Available in Custom Lengths</p> <p>Coiled Cables Available in the Following Lengths Only:</p> <p>006 = 6 ft. (1.83 m) 010 = 10 ft. (3.05 m) 016 = 16 ft. (4.88 m)</p>	<p>D2CG</p>  <p>2 socket MIL connector Portable Measurements</p> <p>E</p>  <p>BNC Jack Connector Portable Measurements, Permanent Mount</p> <p>F</p>  <p>BNC plug connector Portable Measurements, Permanent Mount</p> <p>R2CG</p>  <p>2 Pin MIL Connector Portable Measurements, Permanent Mount</p>	<p>SF</p>  <p>Break-Away Safety Connector</p>

Backed by our Unconditional Lifetime Warranty

www.ctconline.com

