

# SCHENCK COMPATIBLE DATA COLLECTOR CORDSETS

## SCHENCK VIBROTEST 60


### Example Cordset: CB104-C91-006-C79














Black polyurethane jacketed coiled cable, with 6 pin DIN connector to TNC plug connector, 6 foot length extended



### Example Cordset: CB103-C91-015-C79-SF

Black polyurethane jacketed cable with 6 pin DIN connector to TNC plug connector, with safety connector, 15 foot length



Cable Type (see Cables data sheet)	Connector Part Number (see Factory Installed Connectors data sheet)	Cable Length (three digit format)	Terminating Connector Part Number (see Factory Installed Connectors data sheet)	Safety Connector (see page 65 for Safety Connector information)
<p><b>CB103</b></p>  <p>Black Polyurethane 2 Conductor Braided Shield with Drain Wire 250°F (121°C) .245 in (6 mm) AWG=20</p> <p><b>CB104</b></p>  <p>Black Polyurethane, Coiled 2 Conductor Braided Shield 250°F (121°C) .210 in (5 mm) AWG = 22</p> <p><b>CB108</b></p>  <p>Black Polyurethane, Light weight, Coiled 2 Conductor Braided Shield 250°F (121°C) .170 in (4 mm) AWG = 24</p> <p><b>CB110</b></p>  <p>Black Polyurethane, Light weight, 2 Conductor Braided Shield with Drain Wire 250°F (121°C) .175 in (4 mm) AWG = 20</p>	<p><b>C91</b></p>  <p>6 pin DIN Connector Portable Measurements</p>	<p>Select Cable Length Based on Three Digit Numbering System</p> <p>Example Numbering:</p> <p>001 = 1 ft. (.30 m) 005 = 5 ft. (1.52 m) 010 = 10 ft. (3.05 m) 015 = 15 ft. (4.57 m) 025 = 25 ft. (7.62 m) 050 = 50 ft. (15.24 m) 100 = 100 ft. (30.48 m)</p> <p>Straight Cables Available in Custom Lengths</p> <p>Coiled Cables Available in the Following Lengths Only:</p> <p>006 = 6 ft. (1.83 m) 010 = 10 ft. (3.05 m) 016 = 16 ft. (4.88 m)</p>	<p><b>C79</b></p>  <p>TNC Plug Portable Measurements, Permanent Mount</p> <p><b>D2C</b></p>  <p>2 socket MIL connector Portable Measurements</p> <p><b>E</b></p>  <p>BNC Jack Connector Portable Measurements, Permanent Mount</p> <p><b>F</b></p>  <p>BNC plug connector Portable Measurements, Permanent Mount</p> <p><b>J2C</b></p>  <p>2 Socket mini-MIL Connector Portable Measurements</p> <p><b>K2C</b></p>  <p>2 Socket MIL Connector Portable Measurements</p> <p><b>R2C</b></p>  <p>2 Pin MIL Connector Portable Measurements, Permanent Mount</p>	<p><b>SF</b></p>  <p>Break-Away Safety Connector</p>

Backed by our Unconditional Lifetime Warranty

[www.ctconline.com](http://www.ctconline.com)

