

SEMAPI COMPATIBLE DATA COLLECTOR CORDSETS

MX300 DATA LOGGER

Example Cordset: CB110-C350-016-D2C















Light weight, black polyurethane jacketed coiled cable, with 3 pin DIN connector to 2 socket MIL connector, 16 foot length extended



Example Cordset: CB108-C350-001-D2C-SF

Light weight, black polyurethane jacketed cable, with 3 pin DIN connector to 2 socket MIL connector, with safety connector, 1 foot length



Cable Type (see Cables data sheet)	Connector Part Number (see Factory Installed Connectors data sheet)	Cable Length (three digit format)	Terminating Connector Part Number (see Factory Installed Connectors data sheet)	Safety Connector (see page 65 for Safety Connector information)
<p>CB103</p>  <p>Black Polyurethane 2 Conductor Braided Shield with Drain Wire 250° F (121° C) .245 in (6 mm) AWG=20</p>	<p>C350</p>  <p>3 pin DIN connector Portable Monitoring</p>	<p>Select Cable Length Based on Three Digit Numbering System</p> <p>Example Numbering:</p> <p>001 = 1 ft. (,30 m) 005 = 5 ft. (1,52 m) 010 = 10 ft. (3,05 m) 015 = 15 ft. (4,57 m) 025 = 25 ft. (7,62 m) 050 = 50 ft. (15,24 m) 100 = 100 ft. (30,48 m)</p> <p>Straight Cables Available in Custom Lengths</p>	<p>D2C</p>  <p>2 socket MIL connector Portable Measurements</p>	<p>SF</p>  <p>Break-Away Safety Connector</p>
<p>CB104</p>  <p>Black Polyurethane, Coiled 2 Conductor Braided Shield 250°F (121°C) .210 in (5 mm) AWG = 22</p>			<p>E</p>  <p>BNC Jack Connector Portable Measurements, Permanent Mount</p>	
<p>CB108</p>  <p>Black Polyurethane, Light weight, Coiled 2 Conductor Braided Shield 250°F (121°C) .170 in (4 mm) AWG = 24</p>		<p>Straight Cables Available in Custom Lengths</p>	<p>F</p>  <p>BNC plug connector Portable Measurements, Permanent Mount</p>	
<p>CB110</p>  <p>Black Polyurethane, Light weight, 2 Conductor Braided Shield with Drain Wire 250°F (121°C) .175 in (4 mm) AWG = 20</p>		<p>Coiled Cables Available in the Following Lengths Only:</p> <p>006 = 6 ft. (1,83 m) 010 = 10 ft. (3,05 m) 016 = 16 ft. (4,88 m)</p>	<p>J2C</p>  <p>2 Socket mini-MIL Connector Portable Measurements</p>	
<p>CB108</p>  <p>Black Polyurethane, Light weight, Coiled 2 Conductor Braided Shield 250°F (121°C) .170 in (4 mm) AWG = 24</p>			<p>K2C</p>  <p>2 Socket MIL Connector Portable Measurements</p>	
<p>CB110</p>  <p>Black Polyurethane, Light weight, 2 Conductor Braided Shield with Drain Wire 250°F (121°C) .175 in (4 mm) AWG = 20</p>			<p>R2C</p>  <p>2 Pin MIL Connector Portable Measurements, Permanent Mount</p>	

