

PORTABLE MEASUREMENT CORDSETS

GENERAL PURPOSE

Example Cordset: CB108-D2C-016-F

Light weight, black polyurethane jacketed coiled cable, with 2 socket MIL connector to BNC plug connector, 16 foot length extended



Example Cordset: CB110-D2C-010-F-SF

Light weight, black polyurethane jacketed cable, with 2 socket MIL connector to BNC plug connector, with safety connector, 10 foot length



| | | | | | |
|--|---|---|---|---|--|
| CB | | | | | |
| Cable Type (see Cables data sheet) | Connector Part Number (see Factory Installed Connectors data sheet) | Cable Length (three digit format) | Terminating Connector Part Number (see Factory Installed Connectors data sheet) | Safety Connector (see page 65 for Safety Connector information) | |

CB103



Black Polyurethane
2 Conductor
Braided Shield with Drain Wire
250°F (121°C)
.245 in (6 mm)
AWG=20

CB104



Black Polyurethane, Coiled
2 Conductor
Braided Shield
250°F (121°C)
.210 in (5 mm)
AWG = 22

CB108



Black Polyurethane, Light weight, Coiled
2 Conductor
Braided Shield
250°F (121°C)
.170 in (4 mm)
AWG = 24

CB110



Black Polyurethane, Light weight,
2 Conductor
Braided Shield with Drain Wire
250°F (121°C)
.175 in (4 mm)
AWG = 20

D2C



2 socket MIL connector
Portable Measurements

J2C



2 Socket mini-MIL Connector
Portable Measurements

K2C



2 Socket MIL Connector
Portable Measurements

R2C



2 Pin MIL Connector
Portable Measurements,
Permanent Mount

Select Cable Length
Based on Three Digit
Numbering System

Example
Numbering:

001 = 1 ft. (,30 m)
005 = 5 ft. (1,52 m)
010 = 10 ft. (3,05 m)
015 = 15 ft. (4,57 m)
025 = 25 ft. (7,62 m)
050 = 50 ft. (15,24 m)
100 = 100 ft. (30,48 m)

Straight Cables Available
in Custom Lengths

Coiled Cables Available
in the Following Lengths
Only:

006 = 6 ft. (1,83 m)
010 = 10 ft. (3,05 m)
016 = 16 ft. (4,88 m)

D2C



2 socket MIL connector
Portable Measurements

E



BNC Jack Connector
Portable Measurements,
Permanent Mount

F



BNC plug connector
Portable Measurements,
Permanent Mount

FX90



BNC plug connector,
Epoxy Filled, Right Angle
Portable Measurements,
Permanent Mount

J2C



2 Socket mini-MIL Connector
Portable Measurements

K2C



2 Socket MIL Connector
Portable Measurements

R2C



2 Pin MIL Connector
Portable Measurements,
Permanent Mount

